

HNE HiPRESS 50



HiPRESS
Feuerlöscher
Fire Extinguisher
50 L, Foam
A, 10 B

1. Schlauch komplett ausrollen.
Unroll hose completely.
2. Sicherungsschleife(n) ziehen und Kappen(n) entfernen.
Pull locking pin(s) and remove cap(s).
3. Ventile komplett öffnen.
Open valve(s) completely.
4. Richten Sicherungshohlnadel auf Feuerhochdruckstrahlgerät.
Line lock upwards the red safety lever of the trigger.
5. Löschkapule auf den Brandherd richten und auslösen.
Aim the nozzle at base of fire and activate the trigger.

Vorsicht bei elektrischen Anlagen!
Nur bis 1000V! Mindestabstand 1 m!
Nicht auf Menschen oder Tiere zielen! Sicherheitsabstand 3 m!
Hinweise in der Gebrauchsanleitung beachten!
Attention near electrical devices!
Only up to 1000 V! Minimum distance 1 m!
Don't aim at persons or animals! Safety distance 3 m!
Note the instructions for use!

50 LITRES OF MOBILE FIREFIGHTING

The **HiPRESS 50** is a mobile high-performance firefighting system. 50 litres of volume with a vessel on wheels enable mobile firefighting in large areas and rooms. The high working pressure of the **HiPRESS 50** enables a throwing distance of up to 18 m and a throwing height of up to 13 m! Ideal for mobile operation in factories and warehouses!

TECHNICAL SPECS	HiPRESS 50
Filling Volume	50 litres
Propellant	Air, 300 bar/6,8 l
Working Pressure	34 bar, constantly
Throwing Range (water)	up to 18 m
Duration HiPRESS	app. 86 s
Duration HiPRESS	app. 34,5 l/min
Performance	Fire Types A & B
Range of Temperature *	-25°C to 60°C
Distance to Electricity	min. 4 m / max. 1000 V
Hose Length	10 m
Weight (empty)	app. 56 kg
Weight (filled)	app. 106 kg
Height	790 mm
Width	860 mm
Length	700 mm
Certification	SQ 46/15

* with frost-proof foam agent

Fire Types

